TECHNICAL DATA SHEET

Hylastic Strapping

Product description	**Ultra high grade polyester strapping made to the very precise tolerances demanded by some strapping machinery**
Product data	
~ colour	black
~ surface	smooth
~ core size	406 x 150mm (HY714, HY716, HY718)
	200 x 190mm (HYS654, HYS716)
HY714	
~ width	11.1mm
~ thickness	0.51mm
~ length	3,200mtr
~ average break strain	180kg
HY716	
~ width	10.8mm
~ thickness	0.63mm
~ length	2,438mtr
~ average break strain	225kg
HY718	
~ width	11.1mm
~ thickness	0.76mm
~ length	2,134mtr
~ average break strain	270kg
HYS654	
~ width	9.0mm
~ thickness	0.46mm
~ length	3,430mtr
~ average break strain	135kg
HYS716	
~ width	10.8mm
~ thickness	0.63mm
~ length	2,040mtr
~ average break strain	225kg
Tolerances	
~ strap width	+/- 5%
~ strap thickness	+/- 5%
~ break strain	+/- 10%

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.