STRONGHOLD

SPECIFICATION SHEET
ISSUE 1-06.2018

SP50-10B-K

PNEUMATIC ANVIL STAPLER

Versatile air powered stapler with four interchangeable anvils that enable stapling of cardboard cartons, postal tube end caps, blister packs, vegetable tray boxes etc. without damage.

STRONGHOLD

SP50-10B-K

PNEUMATIC ANVIL STAPLER

Provides compression prior to and during entire stapling operation to give a strong, tight closure without damaging the surface of corrugated material. Allows flexibility of staple placement and limits interference of obstacles such as box flanges.

Features:

- Heavy duty steel construction throughout offers reliable performance in industrial packing environments
- Large staple capacity reduces downtime between staple reloading
- 6" x 1" throat
- Air-powered for high-volume usage
- Recommended for use with SHBS9 or SHBS18 box support

Recommended staples:
SB501912
SB501938
SB501958

Specifications

height:	240mm
width:	55mm
length:	370mm
weight:	3.0kg
anvil type:	standard
air pressure requirement:	2.5-3.9kg/cm^3 (36-55 psi)

Staple Specifications

staple sizes:	SB501938 (9.5mm) SB501912 (12mm) SB501958 (16mm)
staple capacity:	220

Anvil Types

Flat
Ideal for cartons, vegetable tray boxes, postal tube end caps etc.

Left Curved
Facilitates stapling of top carton flaps where a conventional anvil would be obstructed.

Raised
Prevents crushing of blister pack edges during stapling.

Right Curved
Similar to the left curved anvil but enabling access from the opposite angle.

For more information on the range of Stronghold® stapling products, please visit:

www.stronghold.eu.com

© Packaging Brands Ltd 2018
Stronghold® is a registered trademark of Packaging Brands Ltd.
We reserve the right to change product specifications without prior notice
Literature re-order code: LIT-PSP070

STRONGHOLD