

OPTIMUM QUALITY MAXIMUM RELIABILITY™



AIR CUSHION SYSTEM

VMAX3

PILLOPAX AIR PILLOW VOID FILL SYSTEM



New generation air pillow system
provides a host of advantages
over traditional loosefill





VMAX3

PILLOPAX AIR PILLOW VOID FILL SYSTEM

Features include:

- > Portable, compact, rugged design
- > Only weighs 13kg
- > Very simple and easy to use controls
- > Suitable for 200 x 200mm and 200 x 100mm Pillopax film
- > The VMAX3 uses our unique high performance Pillopax® films as well as our general purpose Pillopax® film
- > 15 metres per minute inflated pillow output
- > Reliable, consistent pillow throughput



VMAX3 air-pillow systems benefit from:



Reduced storage area required.



User-friendly. Easy recycling and disposal. Ultimate product presentation.



Static protection of your packaged goods - unlike loosefill that can 'settle' allowing goods to migrate during transit.



12 MONTHS PARTS OR RETURN TO BASE WARRANTY AS STANDARD. FOR EXTENDED WARRANTY SEE FOOT OF PAGE.



ENVIRONMENTALLY RESPONSIBLE ALTERNATIVE



USE PILLOPAX® AIR PILLOWS



Specifications

Machine Weight:	13 kg
Machine Dims w x d x h (mm):	320 x 400 x 360
Speed:	15 mtrs/minute
Pillow Sizes (mm):	200 x 200 200 x 100

Standard Pillopax® Film

Code	Pillow size (mm)	Film thickness	Roll length
PPF100	200 x 100	35mu	500mtr
PPF150	200 x 150	35mu	500mtr
PPF200	200 x 200	35mu	650mtr



High Performance Pillopax® Film

> Offers higher burst and puncture resistance than standard film

Code	Pillow size (mm)	Film thickness	Roll length
PPF100HP	200 x 100	mu	500mtr
PPF200HP	200 x 200	mu	500mtr
PPF200-650HP	200 x 200	mu	650mtr



ENVIRONMENTALLY RESPONSIBLE ALTERNATIVE

For more information on the complete range of Optimax® packaging products, please contact your authorised Optimax® distributor or visit:

www.optimaxproducts.com

©Copyright Optimax 2016
We reserve the right to change product specifications without prior notice
Literature re-order code: LIT-PS036

